

BALL VALVES HOT & COLD WATER MIXING UNIT - 3600BM SERIES

SuperKlean now offers a hot & cold water mixing units with ball valves for easier shutoff while maintaining its original characteristics. The unit uses “Y” style body mechanics with lift check valves and ball joint unions for superior flexibility during installation. SuperKlean’s inlet center lines have the same dimensions as most of our competitors’ units. Our units come with a mounting plate for easy behind the unit cleanup, hose rack for easy user access to the hose, and an optional temperature gauge for accurate temperature readings at outlet.

Part #:	Description
3600BM-B	Brass, hot & cold water wall mounted mixer-hose station. Includes ball valves instead of globe valves.
3600BM-B-T	Brass, hot & cold water wall mounted mixer-hose station with adjustable angle temperature gauge. Includes ball valves instead of globe valves.

UNIT NOT FOR USE WITH STEAM

Principal Parts & Materials

Inlet / Outlet: 3/4” NPT

Mixer Body: Brass

Ball Valves: Bronze / 300 Series Stainless Steel

Hose Rack: 300 Series Stainless Steel

Temperature Gauge: (optional) Stainless Steel

Weight: 13 Lbs.

Maximum

Maximum Pressure: 150 PSI

Maximum Temperature: 200°F (93°C)

