

# STANDARD SPRAY NOZZLES - 150 SERIES

SuperKlean spray nozzles have rear mounted levers which reduce hand fatigue and offer smooth lever action. The valve seat in all SuperKlean nozzles is an integral part of the nozzle body.

Variable spray patterns, adjustable from fan spray to solid stream, is one of the many features offered by SuperKlean spray nozzles. Water conservation is assured upon release of lever by the drip-free automatic shutoff feature.

SuperKlean spray nozzles are available in:

- Brass (3 lbs.)
- Anodized Aluminum (1.69 lbs.)
- 300 Series Stainless Steel (2.78 lbs.)



**Standard Aluminum Nozzle**



**Standard Brass Nozzle**



**Standard 300 Series Stainless Steel Nozzle**

Inlet Pressure *(PSIG)	Flow Rate *(GPM)
25	4.63
50	6.88
75	8.61
100	10.07
125	11.41
150	12.52
*Estimated	



**Rating: 150 PSI / 200°F (93°C)  
NOT FOR USE WITH STEAM**

STANDARD NOZZLES	
Part #:	Description
150B-DB	Brass nozzle with dark blue cover
150B-R	Brass nozzle with red cover
150B-W	Brass nozzle with white cover
150A-LB	Anodized aluminum nozzle with light blue cover
150A-R	Anodized aluminum nozzle with red cover
150A-W	Anodized aluminum nozzle with white cover
150S-G	300 series stainless steel nozzle with gray cover
150S-R	300 series stainless steel nozzle with red cover
150S-W	300 series stainless steel nozzle with white cover